



# R717 refrigerant grade ammonia. High quality and natural.



## Introduction

R717 is refrigerant grade high purity ammonia (NH<sub>3</sub>). The product typically is 99.98% pure with minimal levels of moisture (< 200 ppm) and other impurities (< 3 ppm oil), making it ideal for use in all types of refrigeration systems, especially in the air conditioning industry. All cylinders and drums are equipped with dip tube.

## Specifics/facts

Ammonia 3.8 (99,98%). Max 200 ppm H<sub>2</sub>O and oil max 3 ppm.

## Product specification

Cylinder size in litres	Content in kg	Valve	Country	Item number
26	13,8	double	SE/NO/DK	107094
61	32	double	SE/NO/DK/FI/EE/LT/LV	113139
108	57	single	SE/NO/DK/FI/EE/LT/LV	107095
108	57	single (liquid)	SE/NO/DK/FI/EE/LT/LV	107096*
127	Waste		SE/NO/DK	116997**
900	475	2 valves	SE/DK/FI/EE/LT/LV	113233
995	527	2 valves	SE/NO/DK/FI/EE/LT/LV	107587

\* without diptube \*\*waste-cylinder and 61L upon request in SE/NO

## Advantages

- Zero ozone depletion potential and zero global warming potential
- Excellent thermodynamic properties leading to a high energy efficiency
- Wide range of operating temperatures (-50 to +15°C)